



Mounting



Specification



SmartScan Configurations



Find out more at www.thorlux.com/smartscan

LED Characteristics

CRI	80+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	100K-L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	88%
REPLACEABLE	YES
POWER FACTOR	>0.9
LL/CW	103.1

ENERGY EFFICIENCY CLASSIFICATION **B**

For LED characteristics explanation see www.solite-europe.com/led-guide

Surface mounted, front access luminaire designed for clean and sterile environments up to FS209E class 100. IP65 ensures maximum protection is maintained at all times, even when the cover is removed.

Applications

- Clean and sterile environments up to FS209E class 100, ISO 14644 class 5
- Pharmaceutical production
- Pharmacies
- Hospitals
- Laboratories
- Electronics manufacturing
- Semiconductor manufacturing
- Food preparation manufacturing

Construction

- Zinc plated surface mounted steel body
- Chamfered 55mm aluminium diffuser frame, with welded and finished corners
- Polyester powder coated body and frame
- Polycarbonate fire-retardant diffuser, TP(a)
- White EPDM closed cell gaskets

Finish

- RAL9016
- Satin opal diffuser

Features

- Fixed output, 4000K, CRI80 as standard
- Conforms to FS209E class 100, ISO14644 class 5 standard.
- IP65
- LUX Guard, LED Protection
- Removable LED platform for improved sustainability and longer life cycle

Options

- Special RAL colour **
- Anti-bacterial paint **
- 3000K or 6500K LED light engine **
- CRI90 LED light engine **
- Screwless frame. Add '+SCREWLESS'
- Deglaring lens: LG7 compliant, providing <1500cd/m². Replace 'S' suffix with: 'LP' clear polycarbonate 'LG' toughened glass
- Toughened glass front panel: For applications where corrosive cleaning agents may be applied. Glass is supplied in addition to the satin polycarbonate panel. Replace 'S' suffix with 'TGS'

** Available on request, contact sales

Controls Options

- DALI or SmartScan

Emergency Options, 3 hour integral ***

- Standard, Self-test, DALI or SmartScan

*** Central battery, contact sales

Range

LED	CAT. NO.	SIZE	APPROX. kg
26W	GAMMA2226WLED4S	600mm x 600mm	10.5
38W	GAMMA2238WLED4S		
45W	GAMMA2245WLED4S		
54W	GAMMA2254WLED4S		
75W	GAMMA2275WLED4S		
52W	GAMMA4252WLED4S	1100mm x 600mm	19.0
76W	GAMMA4276WLED4S		
90W	GAMMA4290WLED4S		
108W	GAMMA42108WLED4S		
40W	GAMMA4140WLED4S	1220mm x 300mm	12.5
49W	GAMMA4149WLED4S		
64W	GAMMA4164WLED4S		


CIRCUIT TYPE - suffix catalogue number with:

DALI-DIM - DALI dimmable / **SSCAN** - SmartScan e.g. **GAMMA2238WLED4S+DALI-DIM**


EMERGENCY VERSION - suffix catalogue number with:

EM - standard 3 hour integral / **EM-ST** - Emergency Self-test 3 hour integral / **DALI-EM** - DALI 3 hour integral / **SSCAN-EM** - SmartScan 3 hour integral e.g. **GAMMA2238WLED4S+EM**

Dimensions



Photometric Guide



LG7 ENABLING

Luminaire Lumen Output 600x600
26W = 3380lm
38W = 4705lm
45W = 5485lm
54W = 6320lm
75W = 8405lm
Emergency = 422lm ▲

Luminaire Lumen Output 1200x600
52W = 6765lm
76W = 9410lm
90W = 10970m
108W = 12635lm
Emergency = 380lm ▲

SATIN

Luminaire Lumen Output 600x600
26W = 3190lm
38W = 4435lm
45W = 5175lm
54W = 6120lm
75W = 7625lm
Emergency = 396lm ▲

Luminaire Lumen Output 1200x600
52W = 6380lm
76W = 8875lm
90W = 10350lm
108W = 12235lm
Emergency = 356lm ▲

Luminaire Lumen Output 1200x300
40W = 4576lm
49W = 5538lm
64W = 6940lm
Emergency = 376lm ▲

▲ NOTE: Emergency lumen output does not change according to wattage.
(Lumen output for central battery systems will vary according to the installation)

Mounting Arrangement

