


VANDAL RESISTANT RECESSED LED LUMINAIRES FOR GRID AND CUT APERTURE CEILINGS



SPECIFICATION

- Steel body, aluminium frame, finished full polyester non-yellowing satin white RAL 9016 for 24mm exposed tee versions and RAL 9010 for spring tee / Burgess grid options
- Ligature resistant
- Diffuser frame fixed with tamper-resistant pin torx screws
- Satin polycarbonate diffuser
- Optional low glare micropism lens behind clear polycarbonate cover
- Supplied with side arm suspension brackets
- Option to fit 24mm exposed tee grid, plasterboard/cut aperture and spring tee / Burgess grid ceilings
- Fitted with CRI 80+ 4000K or 6500K LEDs
- CRI 90 versions available on request
- Other sizes and wattages available on request

LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	4000K/6500K
RATED LIFE (HOURS)	100K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>90%
REPLACEABLE	YES
POWER FACTOR	>0.9
LL/CW	103.1


ENERGY EFFICIENCY CLASSIFICATION **B**

For LED characteristics explanation see www.solite-europe.com/led-guide

ACCESSORIES

DESCRIPTION	CAT. No
T30 pin Torx bit (Suitable for magnetic bit holder)	KEY 16977

DIMENSIONS



RANGE

	NOMINAL SIZE (mm)	LED	4000K	6500K	APPROX. kg	CIRCUIT
BURGESS GRID	Satin					
	600 x 600	26W	ST 19491	ST 19495	11.0	L/A
		38W	ST 19492	ST 19496	11.0	L/A
	Low Glare					
	600 x 600	26W	ST 19493	ST 19497	11.0	L/A
		38W	ST 19494	ST 19498	11.0	L/A
24MM TEE / PLASTERBOARD	Satin					
	600 x 600	26W	ST 19499	ST 19503	11.0	L/A
		38W	ST 19500	ST 19504	11.0	L/A
	Low Glare					
	600 x 600	26W	ST 19501	ST 19505	11.0	L/A
		38W	ST 19502	ST 19506	11.0	L/A

CIRCUIT TYPE - suffix catalogue number with:

L - non-dimming (LED) / **A** - dimming (DALI) e.g. **ST 19491L** etc.

EMERGENCY VERSION - prefix catalogue number with:

E - Emergency / **T** - AutoTest e.g. **EST 19491L** etc.

Add 0.3kg to weights listed.

INTEGRAL NIGHT LIGHT VERSION - suffix catalogue number with:

N (Can add to A or L versions only) e.g. **ST 19491LN** etc.

MOUNTING ARRANGEMENTS

