



Medica with back trunking section




Medica without back trunking section

RANGE

| NOMINAL SIZE (mm) | LED | LUMINAIRE ONLY | LENGTH (mm) | APPROX. kg | LUMINAIRE COMPLETE WITH BACK TRUNKING | APPROX. kg |
|-------------------|--|----------------|-------------|------------|---------------------------------------|------------|
| 1000 | 2 x 29W uplighter and DALI dimming downlighter | SMD 16376 | 1017 | 4.2 | SMD 16380 | 7.5 |
| 1300 | 2 x 38W uplighter and DALI dimming downlighter | SMD 16378 | 1317 | 6.2 | SMD 16382 | 10.2 |

INTEGRAL NIGHT LIGHT VERSION - suffix catalogue number with: N e.g. SMD 16376N etc.

DIMENSIONS



BEDHEAD LUMINAIRES



SPECIFICATION

- Shallow depth extruded aluminium body with die-cast aluminium ends designed for easy cleaning
- Finished full polyester non-yellowing satin white (RAL 9016)
- Complies with the CIBSE 2008 Hospital Lighting Guide (LG2)
- Separate switching facility for up and down light operation
- Dimmable downlight for patient comfort
- Optional centrally mounted 1W LED night light contained within the lower (downlight) compartment
- Curved and sloping top discourages use as a shelf and helps minimise dust build-up
- Version with back trunking section
- Complies with BS EN 60598-2-25
- Fitted with 4000K LEDs

LED CHARACTERISTICS

| | |
|--------------------|---------------|
| CRI | 80+ |
| COLOUR TEMPERATURE | 4000K |
| RATED LIFE (HOURS) | 50K - L70/B10 |
| PROTECTION | - |
| DRIVER EFFICIENCY | >85% |
| REPLACEABLE | YES |
| POWER FACTOR | >0.90 |
| LL/CW | 77.6 |

For LED characteristics explanation see www.thorlux.com/led-guide